

675 Loader Series

Base Model Includes:

- Depth control indicator.
- Two 2 ¾" bucket cylinders.
- Two 3" lift cylinders Euro/Global bucket adapter.
- Greaseless loader with optional soft ride.
- Third function line sets are complete with a single function hydraulic multi-coupler.

Loader Specifications:

- Lift Capacity Max. Height @ Pivot Pin: **4200 lbs**
- Lift Capacity Max. Height @ 31.5" Forward of Pivot Pin: **2900 lbs**
- Breakout Force @ Ground Line 31.5" Forward of Pivot Pin: **4030 lbs**
- Breakout Force @ Ground Line at Pivot Pin: **5380 lbs at 2500psi**

Tractors Mounted With The Legend 675 Loader:

- 6105M-6115M-6125M
- 6105R-6115R-6125R
- 6130-6230-6330-6430 Premium

The Legend 675 is compatible only with JD tractor models listed that are equipped with JD H310-H340 loader ready mounts, factory controls, valve and tractor half of the three function hydraulic multi-coupler. We do not make tractor mounts for this loader at this time.

Features/Benefits:

- **Greaseless:** Greaseless chrome pins & Nylatron bushings. No maintenance required with a proven track record of providing extended life with the absolute minimum of wear.
- **Bucket Linkage:** Provides greater bucket roll-back angle and force
- **12'10" Lift Height:** Allows selected 4 and 6 Cylinder tractors to load two layers of round bales on a semi-trailer.
- **Soft Ride Option:** Removes the shock loading on the loader, loader mounts, tractor and operator, longer life of the loader/tractor and less operator fatigue. Soft Ride option includes hydraulic hook up from the loader to the tractor valve and contains the loader half of the multi-coupler that matches to the factory coupler.
- **Lower Torque Tube:** Allows for greater hood clearance and clearance of larger weight receivers.
- **Machined Cylinder End Caps:** Provide added strength and durability over welded.



1-800-557-4689 • www.koykermfg.com

1-605-336-1750 • 200 N Cleveland • Lennox, SD 57039

